

TIMES, REGARDLESS OF ROAD CONTOUR AND LOADING.

(C) APPROACHING VEHICLE FROM REAR.

WHENEVER THE DRIVER OF A VEHICLE APPROACHES ANOTHER VEHICLE FROM THE REAR, WITHIN 300 FEET, THE DRIVER SHALL USE A DISTRIBUTION OF LIGHT PERMISSIBLE UNDER THIS TITLE, OTHER THAN THE UPPERMOST DISTRIBUTION OF LIGHT SPECIFIED IN §22-222(A) (1) OF THIS SUFFIX TITLE.

REVISOR'S NOTE: This section presently appears as Art. 66 1/2, §12-223.

Except for required changes in nomenclature, no changes have been made; see General Revisor's Note to this title.

22-224. SINGLE-BEAM ROAD-LIGHTING EQUIPMENT.

HEAD LAMP SYSTEMS THAT PROVIDE ONLY A SINGLE DISTRIBUTION OF LIGHT SHALL BE PERMITTED ON MOTOR VEHICLES MANUFACTURED AND SOLD BEFORE JUNE 1, 1944, INSTEAD OF THE SPECIFIED MULTIPLE-BEAM ROAD-LIGHTING EQUIPMENT, IF THE SINGLE DISTRIBUTION OF LIGHT COMPLIES WITH THE FOLLOWING REQUIREMENTS AND LIMITATIONS:

(1) THE HEAD LAMPS ARE SO AIMED THAT, WHEN THE VEHICLE IS NOT LOADED, NONE OF THE HIGH-INTENSITY PORTION OF THE LIGHT AT A DISTANCE OF 25 FEET AHEAD PROJECTS HIGHER THAN A LEVEL OF 5 INCHES BELOW THE LEVEL OF THE CENTER OF THE LAMP FROM WHICH IT COMES AND, IN NO CASE, HIGHER THAN 42 INCHES ABOVE THE LEVEL ON WHICH THE VEHICLE STANDS AT A DISTANCE OF 75 FEET AHEAD; AND

(2) THE INTENSITY SHALL BE SUFFICIENT TO REVEAL PERSONS AND VEHICLES AT A DISTANCE OF AT LEAST 200 FEET.

REVISOR'S NOTE: This section presently appears as Art. 66 1/2, §12-224.

Except for minimal changes in style and nomenclature, this section has not been revised; see General Revisor's Note to this title.

22-224.1. LIGHTING EQUIPMENT ON MOTORCYCLES.

THE HEAD LAMP OR HEAD LAMPS ON EVERY MOTORCYCLE MAY BE OF THE SINGLE-BEAM OR MULTIPLE-BEAM TYPE, BUT IN EITHER EVENT SHALL COMPLY WITH THE FOLLOWING REQUIREMENTS AND LIMITATIONS:

(1) EVERY HEAD LAMP OR HEAD LAMPS ON A MOTORCYCLE SHALL BE OF SUFFICIENT INTENSITY TO REVEAL A PERSON OR A VEHICLE AT A DISTANCE OF:

(I) NOT LESS THAN 100 FEET, WHEN THE MOTORCYCLE IS OPERATED AT ANY SPEED OF LESS THAN 25 MILES